



"innovation in its most functional form"

PRODUCT DATA SHEET

SWi20/25TE

HYDRAULIC FLANGE SPREADER SPREADING FORCE: 20T (200kN) 1st step 25T (240kN) 4th step SPREADING DISTANCE: 6.0 - 103.5mm (0.24 - 4.0") WEIGHT: 6.4kg (14.02lb)

CAPABILITIES

At 10,000psi – 700bar: 20T spread force (1st step) 24T spread force (4th step)

6.0mm – 87.5mm (0.24" - 3.4") spread over 4 steps (without stepped blocks)

48.5mm – 103.5mm (1.9" - 4.1") spread over 2 steps (with stepped blocks)

6.0mm – 40.0mm (0.24" - 1.6") spread using only 1st step



USER FEATURES

- Practical, portable and lightweight
- Moulded plastic handle for comfort
- Revolving handle to aid horizontal or vertical spreading
- · Offset handle is directly over the centre of mass
- Removable handle for improved access
- Revolving lanyard connection point
 - Swivel hose coupler with elbow improves access by allowing hose to revolve
- Spread indicator markings for clear precise visual progress feedback

SAFETY FEATURES

- No finger pinch-points
- · Increased step depth on upper steps
- Safety lanyard 1.0m (39") length
- Partially recessed coupler reduces coupler vulnerability
- Forged key components for strength and reliability
- · Fail-safe design designated cylinder nose seal failure

MAINTENANCE FEATURES

- Rapid disassembly and assembly
- Quick jaw replacement remove 1 fastener
- Quick tip replacement remove 2 fasteners
- Narrow jaw teeth improved tool wear


SWi20/25TE


HYDRAULIC FLANGE SPREADER




"innovation in its most functional form"

JAW DIMENSIONS (WITHOUT STEPPED BLOCKS ATTACHED)





JAW DIMENSIONS (WITH STEPPED BLOCKS ATTACHED)







- 2 x SWi20/25TE Flange Spreader Wedgeheads
- 2 x 10,000psi (700bar) Hydraulic Cylinders
- 2 x 10,000psi (700bar) Hydraulic Hoses, 2m (78.75") with 90 degree elbow
- 1 x 10,000psi (700bar) HP350D Sealed Hand Pump with Gauge
- 2 x Sets of Safety Blocks
- 2 x Pairs of Stepped Blocks
- 2 x Hex Keys
- 2 x Lanyard
- 1 x Instruction Manual
- 1 x Plastic Carry Case

920mm x 500mm x 205mm (36.2" x 19.7" x 8.1") Gross Kit Weight 32.4kg (71.5lb) Product Code: SWi2025TEMAXSPB



- 1 x SWi20/25TE Flange Spreader Wedgehead
- 1 x 10,000psi (700bar) Hydraulic Cylinder
- 1 x 10,000psi (700bar) Hydraulic Hose, 2m (78.75") with 90 degree elbow
- 1 x 10,000psi (700bar) HP350S Sealed Hand Pump with Gauge
- 1 x Set of Safety Blocks
- 1 x Pair of Stepped Blocks 1 x Hex Key
- 1 x Lanyard 1 x Instruction Manual

1 x Plastic Carry Case



- 1 x SWi20/25TE Flange Spreader Wedgehead
- 1 x 10,000psi (700bar) Hydraulic Cylinder
- 1 x Set of Safety Blocks
- 1 x Pairs of Stepped Blocks
- 1 x Hex Key
- 1 x Lanyard
- 1 x Instruction Manual
- 1 x Plastic Carry Case

580mm x 330mm x 165mm (22.8° x 13.0° x 6.5°) Gross Kit Weight 11.6kg (25.6lb) Product Code: SWi2025TEMIN

920mm x 500mm x 205mm (36.2" x 19.7" x 8.1") Gross Kit Weight 20.7kg (45.7lb) Product Code: SWi2025TESTDSPB